

C T 2.3 L S

| SIZES_ | S (45cm), M (50cm), L (55cm) |
|------------------|---|
| COLOR(S)_ | Denim blue / Rock grey / Night Black |
| FRAME_ | BESV CT 2. Series alloy frame, Shimano Steps and internal battery compatible |
| DRIVE UNIT_ | Shimano E5000 center-motor, 250W rated power, 40Nm of torque, 25km/h maximum assist |
| BATTERY_ | 504Wh integrated Lithium Ion battery, approved for Shimano Service Program, with Smart 2A charger |
| DISPLAY_ | Shimano SC-E5000, left hand mounted, with LCD display |
| FORK_ | SR Suntour Nex-E25, Lockout, Coil damping, tapered alloy steerer, travel 50mm, QR-axle |
| CRANKSET_ | Shimano FC-E5010 for Shimano E5000, 38T Shimano CR-E50 chainring |
| BOTTOM BRACKET_ | Shimano, integrated in motor |
| PEDALS_ | Wellgo pedals with reflectors |
| REAR DERAILLEUR_ | New Enviolo hub |
| SHIFTERS_ | Enviolo manual |
| CASSETTE_ | KMC for Enviolo, 22T |
| CHAIN_ | KMC Z1 EPT |
| WHEELSET_ | Formula CL-1420 front hub, new Enviolo rear hub, CN streight stainless steel spokes, SR DB-30, 700c multichamber alloy rims for disc brakes with 36H |
| TIRES_ | Maxxis Overdrive, 47x622, Silkshield, 60 TPI wire bead with puncture protection, with reflective stripe |
| BRAKESET_ | Shimano MT200, 2-piston hydraulic disc, with 180mm front and rear rotors |
| BRAKE LEVERS_ | Shimano MT201, 3 finger lever |
| HEADSET_ | First, D346S, 1.5" headset, angular contact bearings |
| HANDLEBAR_ | Alloy City-Trekking rise bar, 6066 alloy, 40mm rise, sweep: 20 degree up, 31.8mm clamp |
| STEM_ | 3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp |
| GRIPS_ | Comfortable gel grips with padding |
| SADDLE_ | Selle Royal Rio Moderate |
| SEATPOST_ | Suspension seatpost with anty-sideplay, 40mm travel, 31.6mm diameter, 12mm offset |
| FENDERS_ | Alloy extruded fenders, front & rear 3/4 length, stainless steel hardware |
| HEADLIGHT_ | Lezyne eBike Mini E65, 6-12v, 65 lux, with reflector |
| TAILLIGHT_ | Herrmans H-Cargo, 6-12v, with reflector |
| REAR CARRIER_ | Tubular aluminium carrier, with Snapit platform and spring clamp, H-Cargo rear light mount |

 ${\tt ACCESSORIES_} \quad {\tt Adjustable} \ kickstand, Chainguard$

250°

50^{MA}

40^{NM}
TORQUE

504^{wh}

E-SYSTEM

_Efficient Shimano E5000 motor with long lasting Darfon 504Wh battery.

GEARING

_Always on right gear thanks to Enviolo inner gear hub.

COLORS

_Three color version to choose.