

CT 2.1



| | |
|------------------|---|
| SIZES_ | M (50cm), L (55cm), XL (60cm) |
| COLOR(S)_ | Steel grey |
| FRAME_ | BESV CT 2.Series alloy frame, Shimano Steps and internal battery compatible |
| DRIVE UNIT_ | Shimano EP600 center-motor, 250W rated power, 85Nm of torque, 25km/h maximum assist |
| BATTERY_ | 504Wh integrated Lithium Ion battery, approved for Shimano Service Program, with Smart 2A charger |
| DISPLAY_ | Shimano SC-E5003, left hand mounted, with LCD display |
| FORK_ | SR Suntour Nex-E25, Lockout, Coil damping, tapered alloy steerer, travel 50mm, QR-axle |
| CRANKSET_ | Samox for Shimano Steps, 38T chainring |
| BOTTOM BRACKET_ | Shimano, integrated in motor |
| PEDALS_ | Wellgo pedals with reflectors |
| REAR DERAILLEUR_ | Enviolo Trekking, 380% gear ratio |
| SHIFTERS_ | Enviolo manual |
| CASSETTE_ | KMC for Enviolo, 18T |
| CHAIN_ | KMC E101 EPT |
| WHEELSET_ | Formula CL-1420 front hub, Enviolo Trekking 380% gear ratio rear hub, 700c multichamber alloy rims 36H |
| TIRES_ | Maxxis Overdrive, 47x622, Silkshield, 60 TPI wire bead with puncture protection, with reflective stripe |
| BRAKESSET_ | Hydraulic disc brake, 2-piston, 180mm front and rear rotors |
| BRAKE LEVERS_ | 2 finger hydraulic disc brake lever |
| HEADSET_ | First, D346S, 1.5" headset, angular contact bearings |
| HANDLEBAR_ | Alloy City-Trekking rise bar, 6066 alloy, 40mm rise, sweep: 20 degree up, 31.8mm clamp |
| STEM_ | 3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp |
| GRIPS_ | Comfortable gel grips with padding |
| SADDLE_ | Selle Royal Rio Moderate |
| SEATPOST_ | Suspension seatpost with anty-sideplay, 40mm travel, 31.6mm diameter, 12mm offset |
| FENDERS_ | Alloy extruded fenders, front & rear 3/4 length, stainless steel hardware |
| HEADLIGHT_ | Lezyne eBike Mini E65, 6-12v, 65 lux, with reflector |
| TAILLIGHT_ | Herrmans H-Cargo, 6-12v, with reflector |
| REAR CARRIER_ | Tubular aluminium carrier, with Snapit platform and spring clamp, H-Cargo rear light mount |
| ACCESSORIES_ | Adjustable kickstand, Chainguard |

380[%]
GEAR RATIO

50^{MM}
SUSPENSION
TRAVEL

85^{NM}
TORQUE

504^{WH}
BATTERY

MOTOR

_Powerful EP600 engine from Shimano is delivering up to 85Nm of torque.

COMFORT

_Adjustable stem, suspension seatpost and city type saddle will provide comfort in everyday riding.

SAFETY

_Powerful lights from Lezyne and Herrmans keeps you safe when riding.