

CT 2.2 LS



SIZES_	S (45cm), M (50cm), L (55cm)
COLOR(S)_	Snow white
FRAME_	BESV CT 2.Series alloy frame, Shimano Steps and internal battery compatible
DRIVE UNIT_	Shimano E6110 center-motor, 250W rated power, 60Nm of torque, 25km/h maximum assist
BATTERY_	504Wh integrated Lithium Ion battery, approved for Shimano Service Program, with Smart 2A charger
DISPLAY_	Shimano SC-E5000, left hand mounted, with LCD display
FORK_	SR Suntour Nex-E25, Lockout, Coil damping, tapered alloy steerer, travel 50mm, QR-axle
CRANKSET_	Samox for Shimano Steps, 38T chainring
BOTTOM BRACKET_	Shimano, integrated in motor
PEDALS_	Wellgo pedals with reflectors
REAR DERAILLEUR_	Enviolo City, 310% gear ratio
SHIFTERS_	Enviolo manual
CASSETTE_	KMC for Enviolo, 20T
CHAIN_	KMC E101 EPT
WHEELSET_	Formula CL-1420 front hub, Enviolo City 310% gear ratio rear hub, 700c multichamber alloy rims 36H
TIRES_	Maxxis Overdrive, 47x622, Silkshield, 60 TPI wire bead with puncture protection, with reflective stripe
BRAKESET_	Shimano MT200, 2-piston hydraulic disc, with 180mm front and 160mm rear rotors
BRAKE LEVERS_	Shimano MT201, 3 finger lever
HEADSET_	First, D346S, 1.5" headset, angular contact bearings
HANDLEBAR_	Alloy City-Trekking rise bar, 6066 alloy, 40mm rise, sweep: 20 degree up, 31.8mm clamp
STEM_	3D Forged alloy City-Trekking stem, adjustable 0-90 degree, 31.8mm clamp
GRIPS_	Comfortable gel grips with padding
SADDLE_	Selle Royal Rio Moderate
SEATPOST_	Suspension seatpost with anty-sideplay, 40mm travel, 31.6mm diameter, 12mm offset
FENDERS_	Alloy extruded fenders, front & rear 3/4 length, stainless steel hardware
HEADLIGHT_	Lezyne eBike Mini E65, 6-12v, 65 lux, with reflector
TAILLIGHT_	Herrmans H-Cargo, 6-12v, with reflector
REAR CARRIER_	Tubular aluminium carrier, with Snapit platform and spring clamp, H-Cargo rear light mount
ACCESSORIES_	Adjustable kickstand, Chainguard

310^{SR}
GEAR RATIO

50^{MM}
SUSPENSION
TRAVEL

60^{NM}
TORQUE

504^{WH}
BATTERY

E - SYSTEM

_Powerful Shimano E6110 motor with long lasting Darfon 504Wh battery.

T I R E S

_On the safe side with the Maxxis Overdrive.

B R A K E S

_Hydraulic disc brake with 180/160mm rotors.