



## TCE 1.1

SIZES_	S (41.5cm), M (43cm), L (46cm)
COLOR(S)_	Shadow black with night black
FRAME_	Dual-suspension BESV TCE Series frame, carbon front and rear triangle, Shimano Steps and internal battery compatible
DRIVE UNIT_	Shimano EP801 center-motor, 250W rated power, 85Nm of torque, 25km/h maximum assist
BATTERY_	720Wh integrated Lithium Ion battery, approved for Shimano Service Program, with Smart 4-5.6A charger
DISPLAY_	Shimano SC-EM800, center mounted, with LCD display, Bluetooth and ANT private connectivity, left hand switch
FORK_	Fox 38 Ebike Performance Elite Float, 38mm stanchions, Air damping, 1.1/8"-1.5" tapered alloy steerer, travel 160mm
REAR SHOCK_	Fox Performance Elite Float X, 205x60, air spring, 150mm rear wheel travel
CRANKSET_	Shimano FC-EM8150 for Shimano EP801, Shimano CRE80 34T chaining
BOTTOM BRACKET_	Shimano, integrated in motor
PEDALS_	Wellgo, alloy body, ball bearings
REAR DERAILLEUR_	Shimano Deore XT RD-M8100, 12 speed
SHIFTERS_	Shimano Deore XT SL-M8100, 12 speed
CASSETTE_	Shimano SLX CS-M7100, 12 speed, 10-51T
CHAIN_	KMC e12Turbo, with Quick-Link
WHEELSET_	Race Face Aeffect-R, eMTB wheelset, front: 29"/ rear: 27.5+, Boost hubs spacing, Race Face multichamber alloy rims 32H
TIRES_	Maxxis Minion DHF, 29"x2.5" / Minion DHR II, 27"x2.6", 3C Maxxterra Compound, EXO+ Protection, Tubeless, 120 TPI foldable
BRAKESET_	Shimano Deore XT M8120, 4-piston hydraulic disc, with 203mm front and rear rotors
BRAKE LEVERS_	Shimano Deore XT M8100, 2 finger lever
HEADSET_	Acros, AZX-581, 1.5" headset, angular contact bearings, integrated cable routing
HANDLEBAR_	E-MTB reis bar, 6066 alloy, 15mm rise, sweep: 7 degree back, 35mm clamp
STEM_	E-MTB 3D Forged alloy stem, 35mm clamp, for internal cable routing
GRIPS_	Race Face Half-Nelson
SADDLE_	Selle Italia Model-X Superflow eBike
SEATPOST_	Fox Transfer Performance Elite dropper post with remote lever, travel: 175mm, 30.9mm diameter, 0mm offset

12

SPEED

160<sup>MM</sup>SUSPENSION  
TRAVEL85<sup>Nm</sup>

TORQUE

720<sup>WH</sup>

BATTERY

### FRAME

\_Fully carbon front and rear triangle of frame together designed with excellent kinematic around 160mm and 150mm of travel and mullet wheel size set-up.

### SUSPENSION

\_Custom-tune pure Fox Performance Elite suspension line with 160mm front and 150mm rear wheel travel.

### DRIVETRAIN

\_High-performance Shimano XT with 12-speed SLX cassette.