



TRX 1.3

SIZES_	S (42.5cm), M (46cm), L (49cm)
COLOR(S)_	Rock grey with night black
FRAME_	Hard-tail BESV TRX Series alloy frame, Shimano Steps and internal battery compatible
DRIVE UNIT_	Shimano EP600 center-motor, 250W rated power, 85Nm of torque, 25km/h maximum assist
BATTERY_	630Wh integrated Lithium Ion battery, approved for Shimano Service Program, with Smart 4-5.6A charger
DISPLAY_	Shimano SC-E5003, left hand mounted, with LCD display
FORK_	SR Suntour XCM34, 34mm stanchions, Lockout, Coil damping, 1.1/8"-1.5" tapered alloy steerer, 120mm travel
CRANKSET_	Samox for Shimano Steps, 34T chainring
BOTTOM BRACKET_	Shimano, integrated in motor
PEDALS_	Wellgo, alloy body, ball bearings
REAR DERAILLEUR_	Microshift XLE 11, 11 speed
SHIFTERS_	Microshift XLE 11, 11 speed
CASSETTE_	Microshift XLE 11, 11 speed, 11-46T
CHAIN_	KMC e11Turbo, with Quick-Link
WHEELSET_	Formula CL-811 front hub, Formula CL-3248 rear hub, Boost hubs spacing, WTB STi27 29" multichamber alloy rims 32H
TIRES_	Maxxis Ardent, 29"x2.4", Normal Compound, EXO, 60 TPI foldable, Tanwall sides
BRAKESSET_	Hydraulic disc brake, 2-piston, 180mm front and rear rotors
BRAKE LEVERS_	2 finger hydraulic disc brake lever
HEADSET_	Acros, AZX-581, 1.5" headset, angular contact bearings, integrated cable routing
HANDLEBAR_	E-MTB reis bar, 6066 alloy, 4mm rise, sweep: 7 degree back, 31.8mm clamp
STEM_	E-MTB 3D Forged alloy stem, 31.8mm clamp, for internal cable routing
GRIPS_	E-MTB gel grips with padding and BESV clamp
SADDLE_	Selle Italia X3 eBike
SEATPOST_	Promax SP-726, 31.6mm diameter

11
SPEED

120^{MM}
SUSPENSION
TRAVEL

85^{Nm}
TORQUE

630^{WH}
BATTERY

E - SYSTEM

_Powerful and light Shimano EP600 motor with long lasting Darfon 630Wh battery.

SUSPENSION

_Smooth ride thanks to Suntour XCM front fork.

BRAKES

_Hydraulic disc brake with 180mm rotors.