



# TRS 130 Urban 1.3

|                  |   |
|------------------|---|
| SIZES_           | S (40cm), M (42.5cm), L (44.5cm), XL (46cm)   |
| COLOR_           | Metallic steel with black satin   |
| FRAME_           | Full-suspension BESV TRS Series smooth welded alloy frame, Shimano Steps and internal battery compatible          |
| DRIVE UNIT_      | Shimano EP600 center-motor, 250W rated power, 85Nm of torque, 25km/h maximum assist                               |
| BATTERY_         | 708 Wh integrated Lithium Ion battery, approved for Shimano Service Program, with Smart 4-5.6A charger            |
| LOCK_            | Abus T82 battery key-lock   |
| DISPLAY_         | Shimano SC-EN500, left hand mounted, with LCD display   |
| FORK_            | SR Suntour Zeron35, 35mm stanchions, Lockout, Air damping, 1 1/8"-1.8" tapered alloy steerer, travel 130mm        |
| REAR SHOCK_      | Rock Shox Deluxe Select R, 210x55mm, Debon Air, 130mm rear wheel travel   |
| CRANKSET_        | Samox for Shimano Steps, 34T chainring  |
| BOTTOM BRACKET_  | Shimano, integrated in motor  |
| PEDALS_          | Wellgo, alloy body, ball bearings   |
| REAR DERAILLEUR_ | Shimano CUES RD-U6000, 11 speed   |
| SHIFTERS_        | Shimano CUES SL-U6000, 11 speed   |
| CASSETTE_        | Shimano CUES CS-LG400, 11 speed, 11-50T   |
| CHAIN_           | Shimano CN-LG500, with Quick-Link   |
| WHEELSET_        | Shimano HB-MT400 front hub and FH-MT400-B rear hub, Boost hubs spacing, WTB STi27 29" multichamber alloy rims 32H |
| TIRES_           | Schwalbe Johnny Watts, 29x2.35", Addix, Race Guard, 67 TPI wire bead with reflective stripe                       |
| BRAKESET_        | Shimano MT420/MT410, 4/2-piston hydraulic disc, with 203mm front and rear rotors                                  |
| BRAKE LEVERS_    | Shimano MT4100, 2 finger lever  |
| HEADSET_         | Acros, AZX-581, 1.8" headset, angular contact bearings, integrated cable routing                                  |
| HANDLEBAR_       | E-MTB rizer bar, 6066 alloy, 15mm rise, sweep: 7° back, 35mm clamp  |
| STEM_            | E-MTB 3D Forged alloy stem, 35mm clamp, for internal cable routing  |
| GRIPS_           | E-MTB gel grips with padding and BESV clamp   |
| SADDLE_          | Selle Italia Max S5 Superflow   |
| SEATPOST_        | Kind Shock e10, 30.9mm diameter   |
| FENDERS_         | Alloy extruded fenders, front & rear 3/4 length, stainless steel hardware   |
| HEADLIGHT_       | Lezyne e-bike Mini E65, 6-12V, 65 Lux, with reflector   |
| TAILLIGHT_       | Herrmans H-Cargo, 6-12V, with reflector   |
| REAR CARRIER_    | Tubular aluminium carrier, with MIK platform and spring clamp, H-Cargo rear light mount                           |
| ACCESSORIES_     | Adjustable kickstand  |



## FRAME

\_Redesigned alloy frame with improved geometry and very efficient 4-bar suspension system developing 130mm of suspension travel.

## E - SYSTEM

\_Powerful and light Shimano EP600 motor with new generation 708Wh battery.

## SUSPENSION

\_Suntour Zeron air front fork and Rock Shox Deluxe rear damper is a perfect set blending excellent control, agility and comfort.