

JF1

SPECIFICATION

Sizes	M (45.5cm), L (52.5cm)
Color	Matt gray with white decals
Frame	BESV premium alloy frame, with down tube for integrated Darfon battery, for rear hub motor, tapered 1 1/8" - 1.5" head tube, post disc mount, cold-forged dropout and replaceable hanger
Drive Unit	Bafang rear hub motor with speed sensor, 250W rated power, 25km/h maximum assist
Battery	Darfon lightweight integrated battery, removable, 252Wh with 2A charger
Display	BESV HMI display with Smart APP Mode, USB port and wireless connectivity
Fork	Alloy straight blade, road type, rigid fork for post mount disc brakes
Crankset	BESV crank, 44T chainring, 170mm length, with chainring guard
Bottom Bracket	Bafang torque sensor bottom bracket, square type
Pedals	Wellgo C227DU, with reflectors
Rear Derailleur	Shimano XT 10 speed
Shifters	Shimano XT 10 speed
Cassette	Shimano Tiagra 10 speed, 11-34T
Chain	KMC e10 EPT
Wheelset	KT front hub, Bafang hub motor for 6 bolt disc brakes, straight stainless steel spokes, 700c multichamber alloy rims for disc brakes with 36H
Tires	Duro Easy Ride, 700x35c, wire bead, with reflective stripes
Brakeset	Shimano BL-RS600 / BR-RS405 set, flat bar hydraulic disc brakes
Brake Levers	Shimano flat bar hydraulic brake levers
Headset	FSA Orbit C-40, 1 1/8-1.5" headset, ACB bearings
Handlebar	Alloy rise bar, 2014 alloy, 31.8mm clamp, width: 600mm
Stem	Road alloy stem, 31.8mm clamp
Grips	Sport grips with padding
Saddle	Sport saddle with Super Light Foam padding
Seatpost	Alloy micro-adjust, 27.2mm diameter, 17mm offset
Fenders	Alloy extruded fenders, front & rear 3/4 length, stainless steel hardware
Rear Carrier	Compact style tubular aluminium carrier, with platform.