

# TR 1.5

## SPECIFICATION

Sizes	Step-Over: L (55cm), XL (60cm) / Low-Step: S (45cm), M (50cm), L (55cm)
Color	Dark blue metallic with cream decals
Frame	BESV premium alloy frame with down tube for integrated Darfon battery, Shimano center-motor with protection cover, tapered 1 1/8" - 1.5" head tube, post disc mount, cold-forged dropout and replaceable hanger
Drive Unit	Shimano E-6100 center-motor, 250W rated power, 60Nm of torque, 25km/h maximum assist
Battery	Darfon integrated battery, 418Wh with 2A charger
Display	Shimano E-6100 center mounted LCD display with Bluetooth™ and ANT+ private connectivity
Fork	RST, Coil damping, tapered alloy steerer, travel 50mm
Crankset	Shimano E6100, 38T chainring
Bottom Bracket	Shimano, integrated in motor
Pedals	Wellgo C316DU with reflectors
Rear Derailleur	Shimano Altus 9 speed
Shifters	Shimano Altus 9 speed
Cassette	Shimano Altus 9 speed, 11-34T
Chain	KMC e9 EPT
Wheelset	Shimano HB-TX505 front hub and rear hub, for Center Lock disc brakes, straight stainless steel spokes, 700c multichamber alloy rims for disc brakes with 36H
Tires	Schwalbe Energizer Plus Performance, 700×47c, Addix compound, 67 EPI wire bead, with reflective stripe
Brakeset	Shimano MT201, 2-piston hydraulic disc, with 180mm front and 160mm rear rotors
Brake Levers	Shimano MT201, 3 finger lever
Headset	First Components, 1 1/8" - 1.5" headset, retainer bearings
Handlebar	Alloy City-Trekking, rise bar, 2014 alloy, 20mm rise, sweep: 35° up, 31.8mm clamp, width: 680mm
Stem	Alloy City-Trekking, adjustable 0-90°, 31.8mm clamp
Grips	Comfortable gel grips with padding
Saddle	Comfortable saddle with D1 padding
Seatpost	Alloy micro-adjust, 31.6mm diameter, 0mm offset
Fenders	Alloy extruded fenders, front & rear 3/4 length, stainless steel hardware
Headlight	Herrmans MR4 E-Bike, 120 Lumens, 6-12V, with reflector, stem mounted
Taillight	Herrmans H-Cargo, 6-12V, with reflector
Rear Carrier	Integrated with fender, tubular aluminium carrier, with platform and spring clamp, rear light mount
Accessories	Day light integrated in head tube, adjustable kickstand, chainguard